

AFT-4100

Single Line Analog  
Wall mount Phone



- Single line analog wall mount phone.
- Magnetic hook switch.
- Faceplate with customizable hotel logo.
- Coiled cord with optional bungee cord (anti-drop string).

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

- |                |   |
|----------------|---|
| Keys           | <ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Function keys Mute, Volume, Release</li> </ul>  |
| Phone Features | <ul style="list-style-type: none"> <li>• Single Line</li> <li>• Ring indicator</li> <li>• Mute and unmute</li> <li>• One key regaining dial tone</li> <li>• One key handset volume control</li> </ul> |

## 2. Hardware Specifications

- |                 |  |
|-----------------|--|
| LED Indications | • Red color ring indicator   |
| Power           | • Telephone line powered   |
| Ring Voltage    | • 40V RMS minimum  |
| Jacks           | • RJ11 PSTN jack x 1, RJ9 Handset jack x 1                         |
| Line cord       | • 0.7 feet x 1   |
| Bungee cord     | • Coiled cord with optional bungee cord (handset anti-drop string) |
| Size and Weight | • Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 450g             |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968 compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

**Model:**

**AFT-4100**

**AFT-4100-BC**

