

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

AGR-6106-S AGR-6109-S

Single line Analog phone





- Single line analog phone.
- Hearing aid support
- Full duplex speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas, U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEi-EMEA Office

London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

eastern. europe @aei communications. com

AEi-Corporate Office

so.asia@aeicommunications.com

Penang, Malaysia Sales: +604.3994341

Budva, Montenegro Sales: +382 69 891 251

1. Features

Phone Features

Keys (0~9, *, #) Dial keys N/A Line keys

> Function keys Speaker, Volume up/down, 6 or 9 programmable service keys Single line telephone system with speakerphone

Adjustable High-low ringer (2 way selectable switch)

8 steps speakerphone digital volume control

4 steps handset digital volume control

6 non volatile one-touch programmable speed dial memory button

Tone dialing only

Hearing Aid Receiver Compliant

PBX / Standard Line compatible

Multi Purpose LED indicator for Message Waiting and Incoming Ring

Hardware Specifications

Power Line Power (without AC adaptor or battery)

Ring Voltage 40V RMS minimum Jacks RJ11 PSTN jack x 1

Size and Weight Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g

Regulatory **USA** EU

Part 68 **TBR 21 PSTN EMI** FCC Part 15B EN55032 & EN55024 EN60950-1

RoHS Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Telecom TIA/EIA 968-B compliant

Temperature Storage: Low temperature at -10°C High temperature at +60°C Operating Low temperature at +5°C High temperature at +35°C

Model:

AGR-6106-S

AGR-6109-S





