

AMT-6110-SF

Single Line
Analog Phone



- ❑ Single line analog phone.
- ❑ Half duplex speakerphone.
- ❑ 10 customizable service dials.
- ❑ Message waiting key with indicator.
- ❑ Customizable hotel logo and service dials.
- ❑ Support FSK Message Waiting Signal Type

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> <input type="checkbox"/> Dial keys (0~9, *, #) <input type="checkbox"/> Function keys Speaker, Mute, Redial, Flash, Message and Volume up/down <input type="checkbox"/> Programmable Keys 10 Service dial keys
Phone Features	<ul style="list-style-type: none"> <input type="checkbox"/> Mute and Resume <input type="checkbox"/> 10 programmable services dials <input type="checkbox"/> Programmable flash timing <input type="checkbox"/> Red color message waiting indicator for ringing and message waiting <input type="checkbox"/> Handset, Speaker volume control <input type="checkbox"/> Ringer volume switch <input type="checkbox"/> Redial last call

2. Hardware Specifications

LED Indications	<input type="checkbox"/> Speaker, Mute keys and Message waiting indicator
Power	<input type="checkbox"/> Telephone line powered
Jacks	<input type="checkbox"/> RJ11 PSTN jack x 2, RJ9 Handset jack x1,
Ring Voltage	<input type="checkbox"/> 40V RMS minimum
Line Cord	<input type="checkbox"/> 10 feet x 1
Size and Weight	<input type="checkbox"/> Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g
Message Waiting Signal Type	● FSK, High Voltage, Low Voltage, Reverse Polarity

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMC	FCC Part 15B	EN55032 & EN55024
RoHS	<input type="checkbox"/> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	<input type="checkbox"/> Storage: Low temperature at -10°C	High temperature at +60°C
	<input type="checkbox"/> Operating: Low temperature at 0°C	High temperature at +40°C

Model:

ASP-6110-SF

