

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VH-6108-S(A)

Single Line **Analog Phone**



- Single line analog phone.
- Hearing aid support.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas , U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEI-EMEA Office

London, United Kindom Sales: +44 (0) 1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Keys

- Dial keys
- (0~9, *, #)

Phone Features

- Function keys Volume up/down, Mute, Redial, Message and Guest Service Keys x 8 Single line telephone system with speakerphone
- Adjustable High-low ringer (2 way selectable switch)
- 7 steps speakerphone digital volume control
- 8 programmable Guest Service Keys and 1 programmable message key
- 4 steps handset digital volume control
- Multi Purpose LED indicator for Message Waiting and Incoming Ring
- Last number redial (Max up to 31 digitals)
- Microphone Mute with LED indicator
- Hearing Aid Receiver Compatible
- PBX / Standard Line compatible
- Tone dialing only

2. Hardware Specifications

LED Indications

Message waiting indicator

Power

Telephone line powered

Ring Voltage

40V RMS minimum

Jacks

RJ11 Jack x 1, RJ9 jack x 1.

Line cord

10 feet x 1

Size and Weight

Dimensions: 132mm(L) x 208mm(W) x 70mm(H), Weight: 630g

3.	Regulatory	USA	EU
	PSTN	Part 68	TBR 21
	EMC	FCC Part 15B	EN55032 & EN55024 EN60950-1
	RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
	Telecom	TIA/EIA 968-B compliant	
	Temperature	Storage: Low temperature at -10°C	High temperature at +60°C
		Operating Low temperature at +5°C	High temperature at +35°C

Model:

VH-6108-S(A)





