

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VM-6108-S(A)

Single line Analog Phone



- Single line analog phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas , U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEI-EMEA Office

London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Keys

Dial keys (0

(0~9, *, #)

Function keys

Redial, Speaker, Volume +/-, Mute, Message, 8 service dial keys

Phone Features

8 customizable service dials

Handset, speaker and ringer volume control

Red color message key with indicator

Mute and unmute

Redial last call

Ringing indicator

2. Hardware Specifications

LED Indications

Line keys(red), MUTE(red), SPEAKER(red), and MESSAGE(red) keys

Power

Telephone line powered

Jacks

RJ14(RJ11) PSTN jack x 1, RJ9 Handset jack x 1

Ring Voltage

• 40V RMS minimum

Line cord

10 feet x 1

Size and Weight

Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 600g

3. Regulatory

USA

EU

PSTN EMC Part 68 FCC Part 15B TBR 21 EN55032 & EN55024

EN62368-1

RoHS Telecom

Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

TIA/EIA 968-B compliant

Temperature

Storage: Low temperature at -10°C

High temperature at +60°C

Operating Low temperature at +5°C

High temperature at +35°C

Model:

VM-6108-S(A)





