

VS-6104-S(A)

VS-6104-S(A)-EW

Single Line Analog
Speaker Phone



- Single line analog phone.
- Wall mount speaker phone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.
- Optional emergency wire.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys N/A • Function keys Speaker, Mute, Volume UP/Down, 4 service dial keys
Phone Features	<ul style="list-style-type: none"> • Single line telephone system with speakerphone • 4 programmable service dials • Tone dialing only • PBX / Standard Line compatible • Mute and unmute • Ringer volume switch

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> • MUTE(red), SPEAKER(red), MESSAGE(red) keys
Power	<ul style="list-style-type: none"> • Line Power (without AC adaptor or battery)
Ring Voltage	<ul style="list-style-type: none"> • 40V RMS minimum
Line Cord	<ul style="list-style-type: none"> • 0.7 feet x 1
Jacks	<ul style="list-style-type: none"> • RJ11 PSTN jack x 1
Emergency wire	<ul style="list-style-type: none"> • 3.3 feet x 1 (VS-6104(A)-EW only)
Size and Weight	<ul style="list-style-type: none"> • Dimensions: 180mm(L) x 100mm(W) x 27.5 mm(H), Weight: 230g

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
RoHS	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:
VS-6104-S(A)
VS-6104-S(A)-EW

