

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VX-8108-SPBU VX-8208-SPBU 1 or 2 Lines Cordless Handset US/EU DECT Repeater







- EU or US band DECT repeater..
- Two USB charging ports.
- Full duplex speakerphone.
- Customizable hotel logo and service dials.
- 3 hard key and 7 scrollable service dials.
- Compatible with AEI DECT cordless system.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas, U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEi-EMEA Office

London, United Kindom Sales: +44 (0) 1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Standby Time: 240 hrs

Talking Time: 9 hrs

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Handset

Keys		8208	8108	
	 Dial keys 	(0~9, *, #)	(0~9, *, #)	
	 Line keys 	Line1, Line2, END	Line, END	
	 Function 	SPEAKER, VOLUME +/-, HOLD,	SPEAKER,	VOLUME +/-, MUTE,
	keys	MESSAGE, GUEST SERVICES,	MESSAGE,	, GUEST SERVICES,
		EMERGENCY, and 3 soft keys	EMERGEN	CY, and 3 soft keys
Phone Features	 One or Two Lines 3 hard key and 7 scrollable service dials Call Hold and resume(8208 only) 		 Full duplex 	speaker phone
			 Mute and u 	nmute(8108 only)
			 Red color m 	nessage waiting indicator
	 Handset, Spea 	aker, and Ringer volume control	for ringing a	and message waiting
Display Contents	Main logo		 DECT signa 	al status
	 Service dial lis 	t/icons	 Line status 	
	 Battery status: 	power level, charging status	Firmware V	ersion error
DECT Standard	DECT / CAT iq	2.0 compatible	 Channel Sp 	pace: 1728 KHz
	Radio Frequer	ncy Range : 1880~1930 MHz	Bit rate : 11	150 Kbit/s
	• EU: 1881.792	2(ch0)~1897.344(ch9) 10Channels	 Modulation 	: GFSK
	• US: 1921.536	6(ch0)~1928.448(ch4) 5 Channels	 Voice codin 	ng:16 Kbit/s
	RF power : 7 c	dBm		
2. Hardware Sp	ecifications			

Handset

Display	•	2.0" TFT color display
LED Indications	•	Message waiting indic

Message waiting indicator and keypad backlight

3.7v / 900 mAh Li-ion battery Power Charging Time: 5 hrs

Contact pins 3 contact pins for charging and hook detecting

Size and Weight Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (5V / 1A for USB charging) Power

Jacks DC jack x 1, USB type A x 2

Contact pins 3 contact pins for charging

Size and Weight Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g(Base only)

Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g(Handset and base)

<u>ა.</u>	Regulatory	USA	EU			
	RF	FCC Part 15D	EN301406 EN300175 EN300444			
			TS102 527-1/3			
	EMI	FCC Part 15B	EN300386			
	SAR		EN62479			
1	Safety		EN60950-1			
١.	EMC		EN301489-1/6			
	RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)				
	Temperature	 Storage: Low temperature at -10°C 	High temperature at +55°C			
		 Operating Low temperature at +5°C 	High temperature at +35°C			

Model:

VX-8108-SPBU US Repeater VX-8208-SPBU US Repeater VX-8108-SPBU EU Repeater VX-8208-SPBU EU Repeater



