#### Commercial TV UT640S Series (NA)

# UHD Commercial TV with Essential Smart Function

The UT640S series is specifically designed for diverse business environments. By providing compatibility with AV Control systems and DPM (Display Power Management) as well as its smart connectivity, simple user-friendly interface, and UHD picture quality, the UT640S series enhances ease of use while facilitating communications between businesses and their target audiences.



Simple Content Management



Higher Visibility



Better Usability





#### Embedded Content & Group Management


The embedded Content and Group Management System allows you to edit and play content, schedule playlists and groups, and control Signage via remote control, mouse and mobile phone without the use of separate PC or software. This makes content management much easier and more user-friendly.

## SuperSign Control

SuperSign Control is the basic control software, and it can manage up to 100 displays through a single account and server. Power, volume, and scheduling can be remotely adjusted, and firmware updates supported.

## USB Data Cloning

USB data cloning increases efficiency in managing multiple displays for optimal operation since users don't have to set up each display one by one. Once users copy data to a USB device in one display, it can be easily distributed to the other displays through a USB plug-in.







\* This images are provided for illustrative purposes, and the actual GUI may differ.

\* All displays must be connected to the same network.

#### Real-Time Remote Monitoring

Malfunctions or errors can be easily handled through real-time remote care. When an error occurs, notifications can be sent through the SNMP (Simple Network Management Protocol) protocol.

#### Easy Remote Power-On

WOL (Wake-on-LAN) enables users to turn on displays by sending the relevant packet through a network.



#### Perfect Picture Quality and Color

Enjoy Full HD content in 4K ULTRA HD quality, optimized by the 4K Upscaler. The 4K upscaler automatically upgrades Full HD content to ULTRA HD through several upscaling processes so that images look crisp and clear in any viewing situation. This LG TV can also express intense highlights, vivid colors, and deep black hues on the screen through HDR10.



#### Compatibility with AV Control Systems

The UT640S series has been certified Crestron Connected®, proving that it has a higher level of compatibility with professional AV controls. This results in seamless integration and automated control\*, boosting business management efficiency.


## DPM (Display Power Management)


Display Power Management (DPM) can be configured to be On only when there is a TV signal present to manage power more efficiently.





\* It is a network based control system. Available AV control systems may differ by regions.




























\* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering. \* UT640S series basically have a two-pole stand, but it is able to detach the stand from the body, per service environment (can be used as a wall-mount unit).

#### CONNECTIVITY


#### 86" | 75"








#### 65" | 55" | 49" | 43"





\* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.

UT640S	series (NA)	86UT640S	75UT640S	65UT640S	55UT640S	49UT640S	43UT640S
DESIGN	Stand Type	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)
	Front Color	Dark Meteo Titan	Dark Meteo Titan	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black
DISPLAY	Inch	86	75	65	55	49	43
	Resolution	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)
	Brightness (cd/m²)	350	350	400	400	400	300
ROADCASTING SYSTEM	TV Reception	NTSC / ATSC / Clear QAM	NTSC / ATSC / Clear QAM	NTSC / ATSC / Clear QAM	NTSC / ATSC / Clear QAM	NTSC / ATSC / Clear QAM	NTSC / ATSC / Clear QAM
VIDEO	HDR (10 Pro / HLG)	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
AUDIO	Audio Output	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W
	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch
	DOLBY ATMOS	-	-	-	-	-	-
	One Touch Sound Tuning	-	-	-	-	-	-
	LG Sound Sync	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required
UPERSIGN SW COMPABILITY	Content Management Software (SuperSign CMS), Control and Monitoring Software (Control/Control+), Simple Editor						
SIGNAGE FEATURE	Crestron Connected® (Network Based Control), DPM (Digital Power Management), Time Scheduler, RTC (Real Time Clock), NTP sync timer, BEACON, Embedded CM (Contents Manager), Embedded GM (Group Manager)						
MART FEATURE	webOS 4.5, Smart Home (Launcher Bar), Web Browser, Pre-loaded App (YouTube only), Soft AP, Wi-Fi (802.11ac, Bult-in type), Screen Share (Miracast), DIAL, Bluetooth Audio Playback, LG Sound Sync/bluetooth, Mobile Connection Overlay						
HOSPITALITY FEATURE	Public Display Mode, Lock Mode (Limited), Welcome Screen (Splash Image), Insert Image, IP Channel Manager, External Speaker Out (Int/Fixed, 3.5mm, Stereo, Single ended Type (GND, L+, R+), 1W with 80), V-Lan Tag, RJP (Remote Jack Pack) Compatibility (Teleadapt/Guestlink (HDMI CEC)), Moving Picture Playback (SD/HD/Plus HD), Auto Off/Sleep Timer, Smart Energy Saving, Motion Eye Care						
VAINTENANCE FEATURE	USB Cloning, WOL, SNMP, Diagnostics (USB), Simplink (HDMI-CEC (1.4)), IR Out (RS-232C), Multi IR Code						
			USB Cloning, WOL, SNMP, Diagnos	tics (USB), Simplink (HDMI-CEC (1.4)), I	R Out (RS-232C), Multi IR Code		
	Set Side		USB Cloning, WOL, SNMP, Diagnos	tics (USB), Simplink (HDMI-CEC (1.4)), HDMI In 2 (2	· · · ·		
ACK INTERFACE	Set Side Set Rear	HDMI In	(HDCP (2.0)), RF In (tuner), AV In (Phon	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical),	0), USB (2.0)		SNMP)),
ACK INTERFACE		HDMI In 600 x 400	(HDCP (2.0)), RF In (tuner), AV In (Phon	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical),	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servi		SNMP)), 200 x 200
	Set Rear		(HDCP (2.0)), RF In (tuner), AV In (Phon External Speak	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical), ar Out (3.5mm phone jack (Spk-out fixe	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servi d 0.01-1.00W and line out)), Debug (Pl	none Jack Type)	200 x 200
DIMENSION	Set Rear VESA	600 x 400 76.5" x 46.8" x 13.6" / 99.2 lbs	(HDCP (2.0)), RF In (tuner), AV In (Phon External Speak 600 x 400 66.7" x 41.3" x 13.6" / 78 lbs	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical), er Out (3.5mm phone jack (Spk-out fixe 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servi d 0.01-1.00W and line out)), Debug (Pl 300 x 300 49" x 31" x 9.1" / 32 lbs	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs	200 x 200 38.3" x 24.5" x 8.5" / 17.9 lb 973 x 623 x 216 / 8.1 kg
ack Interface Dimension JNIT : mm / kg)	Set Rear VESA W x H x D / Weight (with stand)	600 x 400 76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 44" x 3.7" / 97.4 lbs	(HDCP (2.0)), RF In (tuner), AV In (Phon External Speak 600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.5" x 3.5" / 76.3 lbs	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical), er Out (3.5mm phone jack (Spk-out fixe 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.5" x 3.5" / 47 lbs	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servi d 0.01-1.00W and line out)), Debug (Pl 300 x 300 49" x 31" x 9.1" / 32 lbs 1,244 x 786 x 231 / 14.5 kg 49" x 28.6" x 3.4" / 31.5	xone Jack Type) 300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.6" x 3.2" / 24.5 lbs	200 x 200 38.3" x 24.5" x 8.5" / 17.9 lb 973 x 623 x 216 / 8.1 kg 38.3" x 22.5" x 3.3" / 17.6 lb 973 x 572 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs
DIMENSION	Set Rear VESA W x H x D / Weight (with stand) W x H(H) x D / Weight (without stand)	600 x 400 76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 44" x 3.7" / 97.4 lbs 1,943 x 1,118 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs	(HDCP (2.0)), RF In (tuner), AV In (Phon External Speak 600 × 400 66,7" × 41.3" × 13.6" / 78 lbs 1,693 × 1,048 × 345 / 35.4 kg 66,7" × 38.5" × 3.5" / 76.3 lbs 1,693 × 978 × 88.8 / 34.6 kg 71.8" × 43.9" × 9.1" / 100.8 lbs	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical), er Out (3.5mm phone jack (Spk-out fixe 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.5" x 3.5" / 47 lbs 1,463 x 850 x 87.8 / 21.3 kg 63" x 38.2" x 7.5" / 62.6 lbs	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servi d 0.01-1.00W and line out)), Debug (Pl 300 x 300 49" x 31" x 9.1" / 32 lbs 1,244 x 786 x 231 / 14.5 kg 49" x 28.6" x 3.4" / 31.5 1,244 x 726 x 87.1 / 14.3 kg 53.5" x 33" x 6.9" / 43 lbs	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.6" x 3.2" / 24.5 lbs 1,110 x 650 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs	200 x 200 38.3" x 24.5" x 8.5" / 17.9 lb 973 x 623 x 216 / 8.1 kg 38.3" x 22.5" x 3.3" / 17.6 lb 973 x 572 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs
DIMENSION	Set Rear VESA W x H x D / Weight (with stand) W x H(H') x D / Weight (without stand) W x H x D / Weight (Shipping)	600 x 400 76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 44" x 3.7" / 97.4 lbs 1,943 x 1,118 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs 2,116 x 1,261 x 285 / 59.0 kg	(HDCP (2.0)), RF In (tuner), AV In (Phon External Speak 600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.5" x 35" / 76.3 lbs 1,693 x 978 x 88.8 / 34.6 kg 71.8" x 43.9" x 9.1" / 100.8 lbs 1,823 x 1,116 x 231 / 45.7 kg	HDMI In 2 (2 e Jack Type), Digital Audio Out (Optical), er Out (3.5mm phone jack (Spk-out fixe 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.5" x 3.5" / 47 lbs 1,463 x 850 x 87.8 / 21.3 kg 63" x 38.2" x 7.5" / 62.6 lbs 1,600 x 970 x 190 / 28.4 kg	0), USB (2.0) RS-232C (D-Sub 9pin (Control & Servii d 0.01–1.00W and line out)), Debug (Pl 300 x 300 49" x 31" x 9.1" / 32 lbs 1,244 x 786 x 231 / 14.5 kg 49" x 28.6" x 3.4" / 31.5 1,244 x 726 x 87.1 / 14.3 kg 53.5" x 33" x 6.9" / 43 lbs 1,360 x 835 x 175 / 19.5 kg	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.6" x 3.2" / 24.5 lbs 1,110 x 650 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs 1,193 x 770 x 158 / 134 kg	200 x 200 38.3" x 24.5" x 8.5" / 17.9 lb 973 x 623 x 216 / 8.1 kg 38.3" x 22.5" x 3.3" / 17.6 lb 973 x 572 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs 1,060 x 660 x 152 / 10.2 kg

\* Specifications are subject to change without notice, so please contact LG sales team to verify before ordering.

Download LG C-Display+ Mobile App Google Play Store www.lg.com/b2b
www.youtube.com/c/LGECommercialDisplay

www.facebook.com/LGInformationDisplay

www.linkedin.com/company/lginformationdisplay

LG may make changes to specifications and product descriptions without notice. Copyright © 2020 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. The names of products and brands mentioned here may be the trademarks of their respective owners.

